

This document does not form a contractual engagement on the part of Dosatron International and is for information only.  
Dosatron International reserves the right to alter product specifications without notice.

© DOSATRON INTERNATIONAL S.A.S 2018 - D0025-EN-0419



# D25+ care

**D25AL5N**

Operating flow range: 10L/h mini - 2,5m<sup>3</sup>/h maxi (1/3US Pint/min - 11USGPM)

Maximum operating temperature: 40°C

Operating pressure:

Bar 0,30 - 6  
PSI 4,3 - 85

Injection rate

% 1 - 5  
Ratio 1:100 - 1:20

Concentrated additive injection:

Mini L/h - Maxi L/h 0,1 - 125  
US Fl. Oz/min - mini US GPM - Maxi 0,056 - 0,55

Connections (NPT/BSP male) Ø 20 x 27 mm (3/4")

Hydraulic motor capacity (for every 2 clicks of the piston):  
Around 0,45L (0,118 US Gallons)

# D25+ care

The **NEW** standard



**DOSATRON**  
Animal Health Line



The **NEW**  
standard

# D25+

care



## Food compatibility

CE n°1935/2004  
CE n°2013/2006.



## SmartDosing ready

Compatible with the SmartDosing solution,  
Dosatron's innovation.



## Improved Chemical Resistance

with most of drinking-water treatments commonly  
used in Animal Health.



## Quick locking and coupling systems

Patented systems:  
Easier adjustment & lock of the dosing rate.  
Easy dosing part & seals maintenance (no tool required).



## Calibration possibility around 1% and 5%

Possibility to calibrate above 5% and under 1% required  
by Animal Health certifications & standards.

